

KVV GR5T	
Specification	Description
Engine	EQB190-20 in-line six-cylinder water-cooled, four-stroke, air-to-air supercharged intercooled diesel engine with a power output of 140Kw
Wheelbase	3475+1250mm
Fuel tank	All-steel 145+50L capacity
Clutch	Φ350mm diaphragm spring
Gearbox	A1306 six-speed with mechanical transfer case and two gears
Shifting	Synchronizer shifting with electro-pneumatic control
Axles	3.7 ton front axle and 4 ton double rear axle
Frame section	232× 75×6.5mm
Tires	12.5R20 radial off-road
Cab features	Gun mount and optional power take-off and winch
Suspension	Heavy-duty suspension system with adjustable dampers for off-road performance
Chassis	High-clearance chassis with underbody protection and reinforced frame for rough terrain
Traction control	Enhanced traction control and stability system with adjustable settings for challenging environments
Exterior finish	Durable exterior finish with multiple color options, such as a powder-coated or corrosion-resistant coating
Skid plates	Robust skid plates to protect vital components from damage, with additional protection for the fuel tank and differential
Tires	Tough, all-terrain tires with reinforced sidewalls and run-flat technology
Winch	High-capacity winch with remote control and multiple mounting options for hauling heavy loads or self-recovery
Bumpers	Heavy-duty bumpers with integrated tow hooks and recovery points for towing and recovery operations
Power outlets	Multiple power outlets and electrical connections with high amperage capacity for operating a wide range of equipment and devices
Dimensions	7591×2470×2740 (mm)